



SUNRAY 400 SM

Self-contained UV Flood

P/N UV0446

The *SUNRAY400SM* is a compact UV flood curing system. Unlike competitors units, the *SUNRAY* integrates all system components into a small lamp head which can be easily mounted anywhere on a factory floor, with virtually no cabling or remote control boxes required. Just mount the head, connect the AC line cord, and start curing! The long life 400-Watt metal halide type lamp and parabolic reflector illuminate an 8 x 6 inch curing area with evenly distributed 100mW/cm² UVA light (320–390nm). The head features a convenient carrying handle and sliding height adjustment bracket.



FEATURES

- **Auto-Range AC line input**

The *Auto-Ranging* 90-132 / 180-265 VAC line input makes the *SUNRAY* easy to use in any country, with no wiring changes or voltage select switching required.

- **Lamp power regulation**

The system's switch mode power supply maintains constant lamp power regardless of variations in AC line input or lamp voltages. This regulation provides for repeatable curing times and longer lamp life.

- **Standby mode**

The unit features a standby mode rocker switch, which reduces lamp power by one half. This mode can be used to reduce heat and stray UV light output while the system is not in use.

- **Elapsed hour meter**

A front panel hour meter tracks lamp age, allowing for consistent lamp replacement scheduling.

- **Forced air cooling**

Baffled fan cooling directs air to critical system components, insuring cool operation and high system reliability.



SUNRAY with optional stand & wrap-around shield

Uvitron International, Inc. • 380 Union Street • West Springfield, MA 01089 USA • (413) 731-7835

Web Site: <http://www.uvitron.com/> • Email: info@uvitron.com

All specifications contained herein are preliminary and subject to change without notice